

U. S. Coast Guard Equipment List

ALL EQUIPMENT LISTED BELOW IS USCG ACCEPTED AND MAY BE USED AS LONG AS IN GOOD AND SERVICEABLE CONDITION
 "Approved" items are approved for manufacture - "Former May Use" items are no longer manufactured

164.012 Interior Finish

3M COMPANY 3M CENTER ST. PAUL MN

164.012/0020/0	APPROVED	Aluminum foil tape No. 425, in nominal thickness of 0.08 mm (3 mil).
164.012/0021/0	APPROVED	Aluminum foil tape No. 430, in nominal thickness of 0.05 mm (2 mil).
164.012/0022/0	APPROVED	Aluminum foil tape No. 431, in nominal thickness of 0.05 mm (2 mil).

ALKOR GMBH MORGENSTERNSTRASSE 9 D-8000 MUNCHEN 71 GERMANY

164.012/0083/0	APPROVED	PVC film Type 03801, approved in nominal thickness of 0.15 mm.
----------------	----------	--

ALPHA ASSOCIATES, INC TWO AMBOY AVE PO BOX 128 WOODBRIDGE NJ 07095

164.012/0073/0	APPROVED	Alpha Type "59M" facing in nominal thickness of 9 mil.
----------------	----------	--

BRANTON INDUSTRIES INC 1101 EDWARDS AVENUE JEFFERSON LA 70181

164.012/0112/0	APPROVED	Aluminum foil facing approved in nominal thickness of 0.002 inches (0.05 mm).
164.012/0125/0	APPROVED	"Neptune" Type 3732 navy cloth approved in nominal weight of 14 oz/sq. yard (0.14 kg/sq m).
164.012/0126/0	APPROVED	"Neptune" Type 59M mylar laminate approved in nominal thickness of 0.008 inches (0.2 mm).
164.012/0175/0	APPROVED	"Neptune" Type 3732 navy cloth approved innominal weight of 14 o(0.14 kg/sq m).

CHILDERS PRODUCTS CO PO BOX 505 2061 HARTEL ST LEVITTOWN PA 19057

164.012/0059/0	APPROVED	"Vicryl CP 10" general purpose coating approved at a nominal application rate of 25 sq. ft. per gallon.
164.012/0060/0	APPROVED	"Vicryl CP 11" general purpose coating approved at a nominal application rate of 25 sq. ft. per gallon.
164.012/0061/0	APPROVED	"Chil-Kote CP 17" general purpose coating approved at a nominal application rate of 33.3 sq. ft. per gallon.
164.012/0062/0	APPROVED	"Chil-Perm NF CP 30" general purpose coating approved at a nominal application rate of 50 sq. ft. per ga
164.012/0063/0	APPROVED	"Chil-Perm NF CP 32" general purpose coating approved at a nominal application rate of 50 sq. ft. per ga
164.012/0064/0	APPROVED	"Chil-Seal CP 55A" and "CP 50AHV2" general purpose coating approved at a nominal application rate of 80
164.012/0065/0	APPROVED	"Chil-Perm CP 55" general purpose coating approved at a nominal application rate of 80 sq. ft. per gallon.
164.012/0066/0	APPROVED	"Encacel V" and "Encacel X" general purpose coating approved as a nominal application rate of 16.7 sq. ft. p

COLUMBUS COATED FABRICS DIV OF BORDEN CHEMICAL BORDEN, INC 1280 NORTH GRANT AVE COLUMBUS OH 43216

164.012/0016/0	APPROVED	Vinyl film wall covering, Type K-2, in nominal thickness of 10 mil (0.25 mm).
164.012/0017/0	APPROVED	Vinyl film wall covering material, Type K-2L in nominal thickness of 8 mil (0.2 mm).
164.012/0018/0	APPROVED	Vinyl film wall covering material, Type KL-22 in nominal thickness of 10 mil (0.25 mm).
164.012/0103/0	APPROVED	Vinyl laminated fabric interior finish, Type I-C, specification numbers L5036, L5242(+), and L5256(+) in nom
164.012/0104/0	APPROVED	Vinyl laminated fabric interior finish, Type II-K, specification number L5019, in nominal thickness of 0.025 in
164.012/0111/0	APPROVED	Type I nonwoven vinyl laminated paper wall covering approved in nominal thickness of 11.5 to 14 mil.

COMPAC CORP OLD FLANDERS RD PO BOX 98 NETCONG NJ

164.012/0091/0	APPROVED	Aluminum foil tape approved in maximum thickness of 0.006 inches (0.15 mm).
----------------	----------	---

FORMICA CORPORATION 10155 READING ROAD CINCINNATI OH 45241

164.012/0034/0	APPROVED	Type FR 32 FORMICA laminate in nominal thickness of 0.8 mm (0.032 inches).
164.012/0035/0	APPROVED	Type FR 50 FORMICA laminate (-50/HGF) in nominal thickness of 1.3 mm (0.050 in).
164.012/0036/0	APPROVED	Type FR BK 32 FORMICA laminate (-87/VGF) in nominal thickness of 0.8 mm (0.032 in).
164.012/0037/0	APPROVED	Type FR BK 50 FORMICA laminate (-89/BGF) in nominal thickness of 1.3 mm (0.050 in).

U. S. Coast Guard Equipment List

ALL EQUIPMENT LISTED BELOW IS USCG ACCEPTED AND MAY BE USED AS LONG AS IN GOOD AND SERVICEABLE CONDITION
"Approved" items are approved for manufacture - "Former May Use" items are no longer manufactured

164.012/0055/0	APPROVED	Type FR 32 FORMICA laminate, in nominal thickness of 0.032 inches.	
164.012/0056/0	APPROVED	Type FR 50 FORMICA laminate, in nominal thickness of 0.050 inches.	
164.012/0057/0	APPROVED	Type FR BK 32 FORMICA laminate, in nominal thickness of 0.032 inches.	
164.012/0058/0	APPROVED	Type FR BK 50 FORMICA laminate, in nominal thickness of 0.050 inches.	
FOSTER PRODUCTS CORP AN H B FULLER COMPANY 1200 WOLTERS BOULEVARD ST PAUL MN 55164			
164.012/0011/1	APPROVED	"Foster Insulfas Coating 31-31" general purpose coating at an application	rate of 40 square feet per gallon (1
164.012/0113/0	APPROVED	Weatherite Mastic 36-10 general purpose coating at an application rate of	17 square feet per gallon.
164.012/0114/0	APPROVED	Weatherite Mastic 36-25 general purpose coating as an application rate of	17 square feet per gallon.
164.012/0115/0	APPROVED	Weatherite Mastic 46-10 coating at an application rate of 17 square feet	per gallon.
164.012/0116/0	APPROVED	Weatherite Mastic 46-25 general purpose coating as an application rate of	17 square feet per gallon.
164.012/0117/0	APPROVED	Vapor-Fas 30-15 coating at an application rate of 25 square feet per	gallon.
164.012/0118/0	APPROVED	Sealfas coating 30-36 at an application rate of 40 square feet per gallon.	
164.012/0133/0	APPROVED	"Lagging Adhesive 81-42" general purpose coating approved at an application	rate of 40 square ft/gallon (1 sq.
164.012/0137/0	APPROVED	Type "Duct-Fas 32-19" duct sealant approved in 2 in. (50 mm) strips at an	application rate of 45 sq. ft per gall
GEN CORP POLYMER PRODUCTS PLASTIC FILM DIVISION CHAMBERS AVE JEANETTE PA 15644			
164.012/0072/0	APPROVED	Types "A F12/L28", "B F9/L27", "C F80", "D L27", "E L24", and "F F17/24	vinyl film wall coverings in nomin
164.012/0077/0	APPROVED	Types "Lightweight", "Lightweight T", "Mediumweight", and "Mediumweight T",	vinyl wall covering.
GISLAVED FOLIE AB BOX 518 S-33200 GISLAVED			
164.012/0071/0	APPROVED	"Design 1320" PVC film approved in nominal thickness of 0.15 mm.	
HARDCAST, INC P O BOX 1239 903 W KIRBY WYLIE TX 75098			
164.012/0067/0	APPROVED	"Iron Grip No. 601" duct sealant.	
164.012/0068/0	APPROVED	"No. P301" duct tape.	
HOPEMAN BROTHERS, INC 435 ESSEX AVE WAYNESBORO VA 22980			
164.012/0128/0	APPROVED	Type 604 plastic laminate approved in a nominal thickness of 0.028 inches	(0.7 mm).
164.012/0129/0	APPROVED	Type 607 plastic laminate approved in a nominal thickness of 0.062 inches	(1.6 mm).
INTERNATIONAL MULTI SERVICES 162 HAZELTINE AVE JAMESTOWN NY 14701			
164.012/0076/0	APPROVED	Style 3732-1261 fiberglass cloth facing.	
INTERNATIONAL PAPER DECORATIVE PRODUCTS DIV. HAMPTON SC 29924			
164.012/0004/0	APPROVED	"Micarta" laminated plastic interior finish type PFR-1.	
164.012/0130/0	APPROVED	Micarta Type MFR Laminate (MD-28607), approved in nominal thickness of	0.026 to 0.036 inches (0.6 to 0.
ISOLAMIN AB S-951 84 LULEA SWEDEN			
164.012/0069/0	APPROVED	Type "Design 1320" vinyl film in nominal thickness of 0.15 mm. To be	applied with Bostik AB's "2700-S" a
ISOVOLTA AG A-2351 WIENER NEUDORF AUSTRIA			
164.012/0094/0	APPROVED	"Standard Grade" laminated plastic type interior finish, in 1 mm nominal	thickness.
JOHNS-MANVILLE CORPORATION P O BOX 625005 LITTLETON CO			
164.012/0049/0	APPROVED	aluminum foil facing.	

U. S. Coast Guard Equipment List

ALL EQUIPMENT LISTED BELOW IS USCG ACCEPTED AND MAY BE USED AS LONG AS IN GOOD AND SERVICEABLE CONDITION
"Approved" items are approved for manufacture - "Former May Use" items are no longer manufactured

KEFA HIGHTECH CORP 4501 ROWLETT RD ROWLETT TX 75088

164.012/0122/0 APPROVED Type "Standard" and "Airless" general purpose coatings in an application rate of 0.2 lb/sq. ft (1 kg/cu. meter)

KELLER-NOVOPAN AG INDUSTRIESTRASSE 7 CH 5314 KLEINDOTTINGEN

164.012/0135/0 APPROVED Type "Kellco" high pressure plastic laminate, approved in nominal thickness of 0.8 mm and 1.0 mm.

KWS CO 6764 PRESTON AVE SUITE D LIVERMORE CA 94550

164.012/0033/0 APPROVED No. 332 fiberglass wall covering in nominal 0.38 mm (15 mil) thickness.

164.012/0041/0 APPROVED No. 332 perforated glass fabric in nominal 14 mil thickness.

LIBERTY INSULATION INC 50 HERBERT AVENUE CLOSTER NJ 07624

164.012/0087/0 APPROVED "Liberty PA" perforated fiberglass cloth facing.

164.012/0088/0 APPROVED "Liberty MA" perforated, corrugated aluminum facing.

164.012/0089/0 APPROVED "Liberty CF" fiberglass cloth facing.

164.012/0090/0 APPROVED "Liberty A-2" aluminum foil facing.

MARATHON INDUSTRIES, INC. SUB. OF EAGLE BRIDGES CO. HWY 49 WEST BYRON GA 31008

164.012/0019/1 APPROVED Acrylic vinyl coating, Type EC102, in a application rate of 80 square feet per gallon (1.9 sq. m per liter).

164.012/0079/1 APPROVED "590 Lo-Perm" general purpose coating.

164.012/0110/0 APPROVED Type IC 541 general purpose coating, approved at an application rate of 25 square feet per gallon.

MASCOAT PRODUCTS 3500 EAST T.C. JESTER SUITE N HOUSTON TX 77018

164.012/0140/0 APPROVED "Delta T" marine coating, approved at an application rate not exceeding 55 sq feet/gallon (1.3 sq meter per lite

MON-ECO INDUSTRIES, INC 5 JOANNA COURT EAST BRUNSWICK NJ 08816

164.012/0070/0 APPROVED Eco-Perm Coating 1102.

164.012/0108/0 APPROVED "Eco-Vapor Cote Coating N. F. 55-20" and "Eco-Vapor Cote Coating N. F. 55- 10" general purpose coatings.

164.012/0134/0 APPROVED "Mon-ECO Coating 55-40" general purpose coating.

NATIONAL STARCH AND CHEMICAL CO. 10 FINDERNE AVENUE BRIDGEWATER NJ 08807

164.012/0119/0 APPROVED Aluminum foil facing in mimmm thickness of 0.9 mil. to be applied with "Bondmaster 40-0857" adhesive in

NEVAMAR CORP 8339 TELEGRAPH RD ODENTON MD 21113

164.012/0001/0 APPROVED Nevamar laminated plastic interior finish, Type HR-5, and Type VR-3.

NICHIAS CORP NO 1-26, 1-CHOME SHIBADAIMON, MINATU-KU TOKYO 105 JAPAN

164.012/0097/0 APPROVED Type "31-31" general purpose coating. Approved in nominal application rate of 40 square feet per gallon.

OWENS-CORNING ONE OWENS CORNING PARKWAY TOLEDO OH 43659

164.012/0038/0 APPROVED "Style 332/9466" glass cloth.

164.012/0047/0 APPROVED "Type 3732" fiberglass cloth with AFF 60 finish.

164.012/0048/0 APPROVED "Style 332/9466" fiberglass cloth.

PERSTORP AB S-28480 PERSTORP SWEDEN

164.012/0082/0 APPROVED "Perstorp Standard 0.9 mm" plastic laminate, approved in nominal thickness of 0.9 mm.

PIONEER PLASTICS CORP ONE PIONITE RD P O BOX 1014 AUBURN ME 04211

U. S. Coast Guard Equipment List

ALL EQUIPMENT LISTED BELOW IS USCG ACCEPTED AND MAY BE USED AS LONG AS IN GOOD AND SERVICEABLE CONDITION
"Approved" items are approved for manufacture - "Former May Use" items are no longer manufactured

164.012/0002/0	APPROVED	Laminated plastic interior finish "Pionite Type K61", approved in nominal	0.060 in. (1.52 mm) thickness.
164.012/0012/0	APPROVED	Laminated plastic interior finish "Pionite Type K32", approved in nominal	0.031 in. (0.70 mm) thickness.
164.012/0013/0	APPROVED	Laminated plastic interior finish "Pionite Type K51", approved in nominal	0.052 in. (1.32 mm) thickness.

POLYMER ADHESIVE SEALANT SYSTEMS 2030 CENTURY CENTER BLVD. SUITE 8 IRVING TX 75062

164.012/0121/0	APPROVED	"Air Seal #11" duct sealant at an application rate of 100 sq. feet per	gallon.
----------------	----------	--	---------

POLYREY 24150 LALINDE FRANCE USINE DE COUZE FRANCE

164.012/0054/0	APPROVED	Polyrey melamine plastic laminate in 0.9 to 1.3 mm thickness.
----------------	----------	---

RALPH WILSON PLASTICS CO 600 GENERAL BRUCE DR TEMPLE TX

164.012/0029/0	APPROVED	Type 604 melamine laminate in nominal thickness of 0.028 in. (0.71 mm).
164.012/0030/0	APPROVED	Type 607 melamine laminate in nominal thickness of 0.062 (1.57 mm).
164.012/0046/0	APPROVED	Type 264 plastic laminate in nominal thickness of 0.030 in. (0.76 mm).
164.012/0078/0	APPROVED	Type 606 plastic laminate in nominal thickness of 0.060 inch.
164.012/0092/0	APPROVED	Wilsonart 900 series "Metalcor" laminates consisting of steel or Al cores and high press. laminate in nom. thi
164.012/0105/0	APPROVED	"Wilsonart" Type 605 plastic laminate in nominal thickness of 0.050 in. (1.27 mm).
164.012/0106/0	APPROVED	Wilsonart" Type 266 plastic laminate in nominal thickness of 0.050 in. (1.27 mm).

REILLY-BENTON CO, INC 1645 TCHOUPITOU LAS STREET PO BOX 52346 NEW ORLEANS LA 70152

164.012/0080/1	APPROVED	"Pelican FF" aluminum foil in nominal thickness of 2 mil (0.05 mm).
164.012/0081/1	APPROVED	"Pelican CF" fiberglass cloth facing, in nominal thickness of 5 mil (0.13 mm).

RESOPAL GMBH HANS-BOECKLER-STRASSE 4 GROSS-UMSTADT GERMANY

164.012/0107/0	APPROVED	RESOPAL, Type "F" marine laminate, approved in nominal thickness of 0.8 mm.
----------------	----------	---

RJF INTERNATIONAL CORPORATION OAK GROVE P.O. BOX 657 MARIETTA OH 45750

164.012/0085/0	APPROVED	Types I-G and I-H laminated fabric wall coverings approved in nominal thickness of 0.020 inches (approx
164.012/0086/0	APPROVED	Type 111-D fabric-backed vinyl wall covering approved in nominal thickness of 0.050 inches (approximately 1.
164.012/0127/0	APPROVED	Type II-J vinyl wall covering approved in nominal thickness of 0.025 inches (0.6 mm).

TANIGAKI KOGYO, LTD 975 KOZUKAYAMA TAMON-CHO, TARUMI-KU KOBE 655 JAPAN

164.012/0093/0	APPROVED	Plastic laminate, approved in nominal thickness of 0.1 to 0.3 mm. Applied to noncombustible substrate at ma
----------------	----------	---

THE CLAREMONT CO, INC 174 STATE STREET MERIDEN CT 06450

164.012/0050/0	APPROVED	"Tuffskin #1613" fiberglass reinforced plastic interior finish in nominal thickness of 0.23 mm (0.009 inch).
164.012/0123/0	APPROVED	Type 3732 Navy cloth in nominal weight of 13.5 ounces per square yard.
164.012/0124/0	APPROVED	Aluminum foil facing in nominal thickness of 2 mil.

UNITED MCGILL CORP UNITED SHEET METAL DIV 2000 EAST BROADWAY WESTERVILLE OH 43081

164.012/0075/0	APPROVED	"United Duct Sealer" coating. Nominal film thickness of 0.25 mm (0.010 in.). Application rate 3.8 sq.
164.012/0098/0	APPROVED	"UNI-WEATHER DUCT SEALER" coating. Nominal film thickness of 0.76 mm (0.030 inches). Applicati
164.012/0099/0	APPROVED	"UNI-GRIP DUCT SEALER" coating. Nominal thickness of 0.5 mm (0.020 in.) and 1.0 mm (0.040 in.).
164.012/0100/0	APPROVED	"3155 DUCT SEALER" coating. Nominal thickness of 0.5 mm (0.020) and 1.0 mm (0.040 in).
164.012/0101/0	APPROVED	"UNI-TACK DUCT LINER ADHESIVE" coating. Nominal thickness of 0.15 mm (0.006 in.) Application rat
164.012/0102/0	APPROVED	"UNI-GASKET FLANGE SEALER" coating. Nominal thickness of 0.5 mm (0.020 in.). Application rate

U. S. Coast Guard Equipment List

ALL EQUIPMENT LISTED BELOW IS USCG ACCEPTED AND MAY BE USED AS LONG AS IN GOOD AND SERVICEABLE CONDITION
"Approved" items are approved for manufacture - "Former May Use" items are no longer manufactured

VENTURE TAPE CORP. 38 COMMERCE ROAD ROCKLAND MA 02370

164.012/0120/0	APPROVED	Types "1520CW" and "1521CW" aluminum foil in nominal thickness of 3.5	and 3 mil, respectively.
164.012/0138/0	APPROVED	Type "1519 CW" aluminum foil adhesive tape in nominal thickness of 5 mil	(0.127 mm).
164.012/0139/0	APPROVED	Type "1517 CW" aluminum foil adhesive tape, in nominal thickness of 2.6 mil	(0.066 mm).

VIMASCO CORP PO BOX 516 NITRO WV 25143

164.012/0074/0	APPROVED	Type "713" general purpose coating applied at a rate of 51 square feet	per gallon.
----------------	----------	--	-------------

W S LIBBEY CO #1 MILL STREET LEWISTON ME 04240

164.012/0039/0	APPROVED	Style X-547 and X-630 Fabrics in a nominal weight of 7 ounces per square	yard.
----------------	----------	--	-------

WACO, INC 814 RESEARCH DRIVE PO BOX 2679 NEWPORT NEWS VA 23602

164.012/0043/0	APPROVED	Style 3732 fiberglass cloth with AFF no. 60 finish.	
164.012/0044/0	APPROVED	Style 332/49/9538 fiberglass cloth.	

WESTERN MACARTHUR CO. 2855 MANDELA PARKWAY SUITE "D" OAKLAND CA 94608

164.012/0136/0	APPROVED	Type "3732" fiberglass cloth approved in nominal thickness of 0.0165 in	(0.4 mm).
----------------	----------	---	-----------

WILSONART INTERNATIONAL, INC. 505 SOUTH GENERAL BRUCE DRIVE P. O. BOX 6110 TEMPLE TX 76503

164.012/0131/0	APPROVED	Type 335 Decorative Laminate approved in nominal thickness of 0.028 inches	(0.7 mm).
164.012/0132/0	APPROVED	Type 203 Backer Laminate approved in nominal thickness of 0.030 inches	(0.75 mm).

FOSTER PRODUCTS CORP AN H B FULLER COMPANY 1200 WOLTERS BOULEVARD ST PAUL MN 55164

164.012/0028/0	FORMER-MAY USE	Mariner Coating 30-55.	
----------------	----------------	------------------------	--

RESOPAL GMBH HANS-BOECKLER-STRASSE 4 GROSS-UMSTADT GERMANY

164.012/0095/0	FORMER-MAY USE	laminated plastic.	
----------------	----------------	--------------------	--

164.018 Retroreflective Material

3M COMPANY 3M CENTER ST. PAUL MN

164.018/0001/0	APPROVED	"SCOTCHLITE" SOLAS Grade 3150 (adhesive type) and 6750 (fabric-backed sewab le), Types I and II.	
164.018/0005/0	APPROVED	"Scotchlite" Brand, SOLAS Grade 6750-I Reflective Sheeting, Type I and Type II retroreflective material, comp	
164.018/0006/1	APPROVED	"Scotchlite" Brand, SOLAS Grade 3150-I Reflective Sheeting, Type I and Type II retroreflective material, comp	
164.018/0007/0	APPROVED	"Scotchlite" Brand, SOLAS Grade 6850 Reflective Sheeting, Type I and Type II retroreflective material, com	
164.018/0008/0	APPROVED	"Scotchlite" Brand, SOLAS Grade 3150-A Reflective Sheeting, Type I and Type II retroreflective material, com	

REFLEXITE CORPORATION 315 SOUTH STREET P.O. BOX 1200 NEW BRITAIN CT 06050

164.018/0003/0	APPROVED	"Reflexite FD1402 Polyester Microprism Reflective Sheeting", Types I and II .	
164.018/0004/0	APPROVED	Reflexite type FD1403 or FD1403L acrylated polyester microprism reflective sheeting, with solvent resistant to	

REFLEXITE CORPORATION 315 SOUTH STREET P.O. BOX 1200 NEW BRITAIN CT 06050

164.018/0002/0	FORMER-MAY USE	"Reflexite Polycarbonate Microprism Reflective Sheeting", Type I.	
----------------	----------------	---	--